

Package: rasterDT (via r-universe)

October 31, 2024

Type Package

Title Fast Raster Summary and Manipulation

Version 0.3.2

Date 2022-12-25

Author Joshua O'Brien

Maintainer Joshua O'Brien <joshmobrien@gmail.com>

Description Fast alternatives to several relatively slow 'raster' package functions. For large rasters, the functions run from 5 to approximately 100 times faster than the 'raster' package functions they replace. The 'fasterize' package, on which one function in this package depends, includes an implementation of the scan line algorithm attributed to Wylie et al. (1967) <doi:10.1145/1465611.1465619>.

License GPL (>= 2)

URL <https://github.com/JoshOBrien/rasterDT/>,
<https://joshobrien.github.io/rasterDT/>

BugReports <https://github.com/JoshOBrien/rasterDT/issues/>

Depends methods, raster (>= 3.6-3), data.table

Imports fasterize, sf

Suggests rasterVis

Encoding UTF-8

RoxygenNote 7.2.3

Repository <https://joshobrien.r-universe.dev>

RemoteUrl <https://github.com/joshobrien/rasterdt>

RemoteRef HEAD

RemoteSha dfa6eb419232aa5617204f7f1f2ebdaed3a3ab28

Contents

rasterDT-package	2
cat_to_val	3
crosstabDT	4
fasterizeDT	5
freqDT	6
subsDT	7
zonalDT	9
Index	10

rasterDT-package *Fast Raster Summary and Manipulation*

Description

Fast alternatives to several relatively slow 'raster' package functions. For large rasters, the functions run from 5 to approximately 100 times faster than the 'raster' package functions they replace. The 'fasterize' package, on which one function in this package depends, includes an implementation of the scan line algorithm attributed to Wylie et al. (1967) <doi:10.1145/1465611.1465619>.

Details

The DESCRIPTION file: This package was not yet installed at build time.

Index: This package was not yet installed at build time.

Fast alternatives to several relatively slow raster package functions. For large rasters, the functions run from 5 to approximately 100 times faster than the raster package functions they replace.

Author(s)

Joshua O'Brien

Maintainer: Joshua O'Brien <joshmobrien@gmail.com>

`cat_to_val`*Convert a Categorical Raster to a Value Raster*

Description

Use a categorical raster's RAT to convert it to a continuous raster

Usage

```
cat_to_val(r, which = 2)
```

Arguments

<code>r</code>	A categorical raster with a RAT (returned by <code>levels(r)[[1]]</code>), whose first column contain an entry for every factor level present in the raster. At least one of the subsequent columns should contain numeric values to which each level should be converted.
<code>which</code>	An integer or character string giving the index or name of the column in <code>r</code> 's RAT with the numerical values to which each value in <code>r</code> should be mapped. Default value is 2.

Value

A continuous raster with each category level in `r` replaced by its corresponding value.

Author(s)

Joshua O'Brien

Examples

```
r_cat <- raster(matrix(c(2, 2, 2, 1), ncol = 2))
levels(r_cat) <- data.frame(ID = c(1, 2),
                           VAL1 = c(0.1, 200),
                           VAL2 = c(33, 44))

## Second column of RAT is used by default
r_con1 <- cat_to_val(r_cat)
as.matrix(r_con1)

## Use 'which=' argument for conversion to another RAT column
r_con2 <- cat_to_val(r_cat, which = "VAL2")
as.matrix(r_con2)
```

crosstabDT

Speedy Raster Cross-tabulation

Description

A fast `data.table`-based alternative to `raster::crosstab()`.

Usage

```
crosstabDT(x, y, digits = 0, long = FALSE, useNA = FALSE)
```

Arguments

<code>x</code>	A <code>Raster*</code> object
<code>y</code>	If <code>x</code> has just one layer, a <code>RasterLayer</code> object. Otherwise, if <code>x</code> is a multi-layered <code>RasterStack</code> or <code>RasterBrick</code> , this argument (if any) is unused.
<code>digits</code>	Integer. The number of digits for rounding the values before cross-tabulation. Default is 0.
<code>long</code>	Logical. If <code>TRUE</code> , the results are returned in a 'long' format <code>data.table</code> instead of as a table. Default is <code>FALSE</code> .
<code>useNA</code>	Logical. Should the returned table or <code>data.table</code> include counts of NA values? Default is <code>FALSE</code> .

Value

Either a table or a `data.table` recording the frequency of each combination of raster values.

Author(s)

Joshua O'Brien

Examples

```
r <- raster(nc = 5, nr = 5)
r[] <- runif(ncell(r)) * 2
s <- setValues(r, runif(ncell(r)) * 3)
crosstabDT(r, s)

rs <- r/s
r[1:5] <- NA
s[20:25] <- NA
x <- stack(r, s, rs)
crosstabDT(x, useNA = TRUE, long = TRUE)
```

fasterizeDT

*Polygon Rasterization Using Numeric, Factor, or Character Fields***Description**

A front end for `fasterize::fasterize()`, fixing several of its infelicities.

Usage

```
fasterizeDT(
  x,
  raster,
  field = NULL,
  fun = "last",
  background = NA_real_,
  by = NULL
)
```

Arguments

<code>x</code>	Either an <code>sf::sf()</code> object with a geometry column of POLYGON and/or MULTIPOLYGON objects or a <code>sp::SpatialPolygonsDataFrame</code> object.
<code>raster</code>	A <code>RasterLayer</code> object to be used as a template for the raster output.
<code>field</code>	Character. The name of a column in <code>x</code> , providing a value for each of the polygons rasterized. If <code>NULL</code> (the default), all polygons will be given a value of 1.
<code>fun</code>	Character. The name of a function by which to combine overlapping polygons. Currently takes "sum", "first", "last", "min", "max", "count", or "any". For more details, see <code>?fasterize::fasterize</code> .
<code>background</code>	Value to put in the cells that are not covered by any of the features of <code>x</code> . Default is <code>NA</code> .
<code>by</code>	Character string giving the name of a column in <code>x</code> by which to aggregate layers. If set, <code>fasterizeDT</code> will return a <code>RasterBrick</code> with as many layers as unique values of the <code>by</code> column.

Details

Unlike other functions in this package, `fasterizeDT()` does not use `data.table` to speed up its computations. Instead, it is a wrapper for `fasterize::fasterize()`, intended to address several of that function's limitations.

Most importantly, `fasterizeDT()` takes care to properly handle rasterization operations in which either the template `RasterLayer` or the selected polygon feature field is a factor. Specifically, it always returns a raster whose type (numeric or factor) and levels (if a factor) match that of the spatial polygon attribute indicated by its `field` argument. Second, when `field` specifies an attribute of class "character", `fasterizeDT()` automatically converts it to a factor and returns a factor raster. In this, it is unlike both `fasterize::fasterize()` and `raster::rasterize()`. Finally, unlike `fasterize::fasterize()`, `fasterizeDT()` accepts as inputs either `sf::sf()` objects or `sp::SpatialPolygonsDataFrame` objects.

Value

A raster of the same size, extent, resolution and projection as the supplied raster template. Unlike `fasterize::fasterize()`, `fasterizeDT` returns a raster of the same type as the data in the column of `x` selected by the `field` argument.

Author(s)

Joshua O'Brien

Examples

```
## Load example polygons and prepare a template raster
if (require(raster)) {
  SPDF <- shapefile(system.file("external/lux.shp", package = "raster"))
  llratio <- 1/cos(pi * mean(coordinates(SPDF)[, 2])/180)
  rr <- raster(extent(SPDF),
               resolution = c(llratio * 0.01, 0.01),
               crs = proj4string(SPDF))

  ## An integer-valued field produces a numeric raster
  rInt <- fasterizeDT(SPDF, rr, field = "ID_2")
  plot(rInt, col = colorRampPalette(blues9)(12))

  ## A character-valued field returns a factor raster
  rFac <- fasterizeDT(SPDF, rr, field = "NAME_2")
  if (require(rasterVis)) {
    levelplot(rFac)
  }
}
```

freqDT

Speedy Raster Value Frequency Tabulation

Description

A fast data.table-based alternative to `raster::freq()`.

Usage

```
freqDT(x, ...)

## S4 method for signature 'RasterLayer'
freqDT(x, digits = 0, value = NULL, useNA = c("ifany", "no", "always"), ...)

## S4 method for signature 'RasterStackBrick'
freqDT(
  x,
```

```

  digits = 0,
  value = NULL,
  useNA = c("ifany", "no", "always"),
  merge = FALSE,
  ...
)

```

Arguments

x	A RasterLayer, RasterStack, or RasterBrick object field class.
...	Additional arguments as for <code>raster::writeRaster()</code> , on which this function relies.
digits	Integer for rounding the cell values. Argument is passed to <code>round</code>
value	A single numeric, logical, or NA value. If supplied, <code>freqDT()</code> will only count the number of cells with that value.
useNA	Character (one of "no", "ifany", or "always"). What to do with NA values? See table for details.
merge	Logical. If TRUE the list will be merged into a single data.table.

Author(s)

Joshua O'Brien

Examples

```

r <- raster(nrow = 18, ncol = 36)
r[] <- runif(ncell(r))
r[1:5] <- NA
r <- r * r * r * 5
freqDT(r)

freqDT(r, value = 2)

s <- stack(r, r*2, r*3)
freqDT(s, merge = TRUE)

```

subsDT

Speedy Raster Value Substitution

Description

A fast data.table-based alternative to `raster::subs()`.

Usage

```
subsDT(x, dict, by = 1, which = 2, subsWithNA = TRUE, filename = "", ...)
```

Arguments

<code>x</code>	Categorical RasterLayer with integer values giving field class.
<code>dict</code>	A data.frame or data.table with one (or possibly more) columns corresponding to the values of cells in <code>x</code> and one (or possibly more) columns giving the value to which each value in <code>x</code> should be mapped.
<code>by</code>	Vector of one or possibly more integers or character strings giving the indices or names of the column in <code>dict</code> containing the categorical values in <code>x</code> .
<code>which</code>	Vector of one or possibly more integers or character strings giving the indices or names of the column in <code>dict</code> with the numerical values to which each value in <code>by</code> should be mapped.
<code>subsWithNA</code>	Logical. If TRUE values that are not matched become NA. If FALSE, they retain their original value (which could also be NA). This latter option is handy when you want to replace only one or a few values. It cannot be used when <code>x</code> has multiple layers
<code>filename</code>	Character string giving (optional) file name to which the resultant raster should be written.
<code>...</code>	Additional arguments as for <code>raster::writeRaster()</code> , on which this function relies.

Value

A RasterLayer object.

Author(s)

Joshua O'Brien

Examples

```
r <- raster(ncol = 10, nrow = 10)
r[] <- round(runif(ncell(r)) * 10)
df <- data.frame(id = 2:8, v = c(10, 10, 11, 11, 12:14))
x <- subsDT(r, df)
x2 <- subsDT(r, df, subsWithNA = FALSE)

df$v2 <- df$v * 10
x3 <- subsDT(r, df, which = 2:3)

s <- stack(r, r*3)
names(s) <- c("first", "second")
x4 <- subsDT(s, df)
x5 <- subsDT(s, df, which = 2:3)
```


Description

A fast data.table-based alternative to `raster::zonal()`.

Usage

```
zonalDT(x, z, fun = sum, na.rm = TRUE)
```

Arguments

x	A Raster* to the totality of whose values fun should be applied within each zone.
z	A categorical RasterLayer with codes representing zones.
fun	A name or character string giving the function to be applied to summarize the values by zone. It needs to return a single (or at least a length-one vector). If x might contain any NA values, it should be equipped to handle them. For large rasters, this function needs to be one, like sum() whose value is the same even if carried out in a two-stage application (i.e. first to data subsets and then to the results of those subset applications).
na.rm	Logical. If TRUE, NA values in x are ignored.

Value

A data.table with a summary value for each zone.

Author(s)

Joshua O'Brien

Examples

```
r <- raster(ncols = 10, nrows = 10)
r[] <- runif(ncell(r)) * 1:ncell(r)
z <- r
z[] <- rep(1:5, each = 20)
## for big files, use a character value rather than a function
zonalDT(r, z, "sum")

## for smaller files you can also provide a function
zonalDT(r, z, mean)
zonalDT(r, z, min)

## multiple layers
zonalDT(stack(r, r*10), z, "sum")
```

Index

* package

rasterDT-package, 2
?fasterize::fasterize, 5

cat_to_val, 3
crosstabDT, 4

fasterize::fasterize(), 5, 6
fasterizeDT, 5
freqDT, 6
freqDT, RasterLayer-method (freqDT), 6
freqDT, RasterStackBrick-method
(freqDT), 6

raster::crosstab(), 4
raster::freq(), 6
raster::subs(), 7
raster::writeRaster(), 7, 8
raster::zonal(), 9
rasterDT (rasterDT-package), 2
rasterDT-package, 2
round, 7

subsDT, 7

table, 7

zonalDT, 9